

## Application Advisory:

**Toyo Proxes 4<sup>®</sup> – 275/25ZR26 98W**

**Toyo Proxes 4 – 275/25ZR28 99W**

**Toyo Proxes 4 – 265/25ZR30 99W**

Toyo Tire U.S.A. Corp. (Toyo) is introducing the above passenger car tires for a specific passenger car market segment popularly known as “Hi-Risers.”

## **Important!**

Do not use these tires on pickup trucks or SUVs. They are not designed for such applications. The tire load capacity requirements of these vehicles may exceed the load capacity of these passenger car tires.

## **General Advice for Determining Correct Inflation Pressure:**

Optional, or “plus size” tires, including the subject tires, may require higher inflation pressures than what is indicated on the vehicle’s Tire Information Placard or in the vehicle’s Owner’s Manual. Any optional or “plus size” tire should provide equal or greater load capacity (by inflation) compared to the originally installed (O.E.) tires. Always refer to tire industry load & inflation tables<sup>2</sup> to determine correct inflation values when installing optional or “plus sizes”, or contact Toyo for assistance.

## **WARNING!**

Observe this advice to avoid overloading the tire. Tire overload will contribute to tire fatigue and eventual tire failure. Tire failure may lead to possible injury or death.

## Technical Specifications:

Product Code	SIZE	Rim Width (in.)	Weight (lbs.)	Tread Depth (" / 32nd)	Inflated Dimensions (in.)	
					O.A.D.*	O.A.W.*
197950	275/25ZR26 98W RD	10.0	33	10.0	31.4	10.7
197960	275/25ZR28 99W RD	10.0	37	10.0	33.3	10.7
197970	265/25ZR30 99W RD	9.5	40	9.2	35.2	10.2

\*O.A.D.=Overall Diameter, O.A.W=Overall Width

## Load & Inflation Table:

Single Load per tire in pounds

Size	Tire Load Limit at Various Cold Inflation Pressures															
	PSI	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42
275/25ZR26 98W RD	LBS.	1179	1224	1279	1296	1323	1378	1396	1422	1466	1493	1510	1565	1590	1609	1653
275/25ZR28 99W RD	LBS.	1224	1268	1323	1340	1367	1422	1442	1466	1521	1543	1565	1609	1643	1664	1709
265/25ZR30 99W RD	LBS.	1224	1268	1323	1340	1367	1422	1442	1466	1521	1543	1565	1609	1643	1664	1709

Questions may be directed to Toyo's Consumer Relations Group at:  
1-800-442-8696 (Pacific Time, Monday through Friday, 8am-5pm).

<sup>2</sup> Load and inflation tables are published by The Tire & Rim Association, Inc. 175 Montrose West Ave., Suite 150, Copley, Ohio 44321. Additional information is provided within the Toyo Passenger and Light Truck Tire Product Data Book (order No. 0180310), or at [www.toyo.com](http://www.toyo.com).