

TSD-12-001 August, 2012

Application Advisory:

Toyo Proxes 4® – 275/25ZR26 98W

Toyo Proxes 4 – 275/25ZR28 99W

Toyo Proxes 4 – 265/25ZR30 99W

Toyo Tire U.S.A. Corp. (Toyo) is introducing the above passenger car tires for a specific passenger car market segment popularly known as "Hi-Risers."

Important!

Do not use these tires on pickup trucks or SUVs. They are not designed for such applications. The tire load capacity requirements of these vehicles may exceed the load capacity of these passenger car tires.

General Advice for Determining Correct Inflation Pressure:

Optional, or "plus size" tires, including the subject tires, may require higher inflation pressures than what is indicated on the vehicle's Tire Information Placard or in the vehicle's Owner's Manual. Any optional or "plus size" tire should provide equal or greater load capacity (by inflation) compared to the originally installed (O.E.) tires. Always refer to tire industry load & inflation tables² to determine correct inflation values when installing optional or "plus sizes", or contact Toyo for assistance.

$\mathbf{\dot{M}}$ W A

WARNING!

Observe this advice to avoid overloading the tire. Tire overload will contribute to tire fatigue and eventual tire failure. Tire failure may lead to possible injury or death.

Technical Specifications:

| Product Code | SIZE | Rim Width (in.) | Weight | Tread Depth | Inflated Dimensions (in.) | | | | |
|-----------------|-------------------|---------------------|--------|-------------|---------------------------|---------|--|--|--|
| | SIZE | Kiiii widiii (iii.) | (lbs.) | ("/32nd) | O.A.D.* | O.A.W.* | | | |
| 197950 | 275/25ZR26 98W RD | 10.0 | 33 | 10.0 | 31.4 | 10.7 | | | |
| 197960 | 275/25ZR28 99W RD | 10.0 | 37 | 10.0 | 33.3 | 10.7 | | | |
| 197970 | 265/25ZR30 99W RD | 9.5 | 40 | 9.2 | 35.2 | 10.2 | | | |

^{*}O.A.D.=Overall Diameter, O.A.W=Overall Width

Load & Inflation Table:

Single Load per tire in pounds

| 0! | Tire Load Limit at Various Cold Inflation Pressures | | | | | | | | | | | | | | | |
|-------------------|---|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Size | PSI | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 |
| 275/25ZR26 98W RD | LBS. | 1179 | 1224 | 1279 | 1296 | 1323 | 1378 | 1396 | 1422 | 1466 | 1493 | 1510 | 1565 | 1590 | 1609 | 1653 |
| 275/25ZR28 99W RD | LBS. | 1224 | 1268 | 1323 | 1340 | 1367 | 1422 | 1442 | 1466 | 1521 | 1543 | 1565 | 1609 | 1643 | 1664 | 1709 |
| 265/25ZR30 99W RD | LBS. | 1224 | 1268 | 1323 | 1340 | 1367 | 1422 | 1442 | 1466 | 1521 | 1543 | 1565 | 1609 | 1643 | 1664 | 1709 |

Questions may be directed to Toyo's Consumer Relations Group at: 1-800-442-8696 (Pacific Time, Monday through Friday, 8am-5pm).

² Load and inflation tables are published by The Tire & Rim Association, Inc. 175 Montrose West Ave., Suite 150, Copley, Ohio 44321. Additional information is provided within the Toyo Passenger and Light Truck Tire Product Data Book (order No. 0180310), or at www.toyo.com.