



TOYO TIRES

TOYO TIRES

CELSIUS

THE VARIABLE-CONDITIONS TIRE

ALL SEASON TIRES JUST GOT ONE-UPPED

Now the convenience of an all-season tire and the safety of a winter tire are rolled into one. Introducing Toyo Celsius, the Variable-Conditions tire. With enhanced ice and snow traction, it surpasses the typical all-season tire in winter-weather safety.* And, with a longer tread life than the average winter tire, it's built for convenient year-round use.

TOYOTIRES.COM
TOYO TIRE U.S.A. CORP.
P.O. BOX 6052
CYPRESS, CA 90630
800.442.8696



©2015 Toyo Tire U.S.A. Corp.
Published July 2015

#180749

*See next page for details.

CELSIUS®

VARIABLE-CONDITIONS TIRE

Toyo engineered the Celsius Variable-Conditions tire for better snow and ice traction than typical all-season tires and longer tread life than winter tires. Available in sizes to fit both passenger cars and CUVs, Celsius delivers year-round versatility and convenience plus winter-weather safety in one.

- 60,000-mile treadwear warranty.*
- Inside tread designed for increased snow and ice traction with a higher sipe density for more biting edges, plus slush grooves to evacuate slush and snow.
- Outside tread delivers all-season performance with features that improve traction in dry, wet, and icy conditions as well as reduce irregular wear.
- UTQG for Celsius: 400 A B, 420 A B, 440 A B and 440 A A
- UTQG for Celsius CUV: 500 A A and 520 A A



CELSIUS®

SPECIFICATIONS

CELSIUS® CUV

SPECIFICATIONS

CELSIUS PERFORMS BETTER ON SNOW AND ICE THAN A TYPICAL ALL-SEASON TIRE¹



| TIRE SIZE | LI/SS | SIDEWALL | APPROVED RIM WIDTH RANGE (IN.) | TREAD DEPTH (1/32") | INFLATED DIMENSIONS | | | MAX PRESSURE (PSI) | REVS PER MILE |
|-----------|-------|----------|--------------------------------|---------------------|------------------------|---------------------|----|--------------------|---------------|
| | | | | | OVERALL DIAMETER (IN.) | OVERALL WIDTH (IN.) | | | |
| 185/65R14 | 86H | BSW | 5.0-(5.5)-6.5 | 10.7 | 23.5 | 7.4 | 51 | 885 | |
| 185/60R15 | 84T | BSW | 5.0-(5.5)-6.5 | 10.6 | 23.7 | 7.4 | 44 | 875 | |
| 185/65R15 | 88H | BSW | 5.0-(5.5)-6.5 | 10.7 | 24.4 | 7.4 | 51 | 850 | |
| 195/60R15 | 88H | BSW | 5.5-(6.0)-7.0 | 10.7 | 24.2 | 7.9 | 51 | 858 | |
| 195/65R15 | 91H | BSW | 5.5-(6.0)-7.0 | 10.8 | 25.0 | 7.9 | 51 | 831 | |
| 205/65R15 | 94H | BSW | 5.5-(6.0)-7.5 | 11.0 | 25.5 | 8.2 | 51 | 816 | |
| 205/70R15 | 96T | BSW | 5.0-(6.0)-7.0 | 11.3 | 26.3 | 8.2 | 44 | 789 | |
| 205/75R15 | 97S | BSW | 5.0-(5.5)-7.0 | 11.3 | 27.1 | 8.0 | 44 | 766 | |
| 215/70R15 | 98T | BSW | 5.5-(6.5)-7.0 | 11.3 | 26.9 | 8.7 | 44 | 773 | |
| 225/70R15 | 100T | BSW | 6.0-(6.5)-7.5 | 11.3 | 27.4 | 9.0 | 44 | 757 | |
| 235/75R15 | 105S | BSW | 6.0-(6.5)-8.0 | 11.3 | 28.9 | 9.3 | 44 | 720 | |
| 205/55R16 | 91H | BSW | 5.5-(6.5)-7.5 | 10.7 | 24.9 | 8.4 | 51 | 835 | |
| 205/60R16 | 92H | BSW | 5.5-(6.0)-7.5 | 10.8 | 25.7 | 8.2 | 51 | 809 | |
| 205/65R16 | 95H | BSW | 5.5-(6.0)-7.5 | 11.0 | 26.5 | 8.2 | 51 | 785 | |
| 215/60R16 | 95H | BSW | 6.0-(6.5)-7.5 | 11.0 | 26.1 | 8.7 | 51 | 795 | |
| 215/65R16 | 98T | BSW | 6.0-(6.5)-7.5 | 11.1 | 27.0 | 8.7 | 44 | 769 | |
| 225/60R16 | 98H | BSW | 6.0-(6.5)-8.0 | 11.1 | 26.6 | 9.0 | 51 | 781 | |
| 235/60R16 | 100T | BSW | 6.5-(7.0)-8.5 | 11.2 | 27.1 | 9.4 | 44 | 767 | |
| 235/65R16 | 103T | BSW | 6.5-(7.0)-8.5 | 11.3 | 28.0 | 9.4 | 44 | 741 | |
| 215/50R17 | 91H | BSW | 6.0-(7.0)-7.5 | 10.8 | 25.5 | 8.9 | 51 | 814 | |
| 215/60R17 | 96H | BSW | 6.0-(6.5)-7.5 | 11.0 | 27.2 | 8.7 | 51 | 765 | |
| 225/60R17 | 99H | BSW | 6.0-(6.5)-8.0 | 11.1 | 27.6 | 9.0 | 51 | 752 | |

| TIRE SIZE | LOAD ID | SIDEWALL | LI/SS | APPROVED RIM WIDTH RANGE (IN.) | TREAD DEPTH (1/32") | INFLATED DIMENSIONS | | | MAX PRESSURE (PSI) | REVS PER MILE |
|------------|---------|----------|-------|--------------------------------|---------------------|------------------------|---------------------|----|--------------------|---------------|
| | | | | | | OVERALL DIAMETER (IN.) | OVERALL WIDTH (IN.) | | | |
| 225/55R17 | XL | BSW | 101V | 6.0-(7.0)-8.0 | 11.0 | 26.8 | 9.2 | 50 | 776 | |
| 225/60R17 | SL | BSW | 99V | 6.0-(6.5)-8.0 | 11.1 | 27.6 | 9.0 | 51 | 752 | |
| 225/65R17 | SL | BSW | 102H | 6.0-(6.5)-8.0 | 11.2 | 28.5 | 9.0 | 51 | 729 | |
| 235/55R17 | XL | BSW | 103V | 6.5-(7.5)-8.5 | 11.1 | 27.2 | 9.6 | 50 | 765 | |
| 235/60R17 | SL | BSW | 102H | 6.5-(7.0)-8.5 | 11.2 | 28.1 | 9.4 | 51 | 739 | |
| 235/65R17 | XL | BSW | 108V | 6.5-(7.0)-8.5 | 11.3 | 29.1 | 9.4 | 50 | 715 | |
| P245/65R17 | SL | BSW | 105H | (7.0)-8.5 | 11.3 | 29.5 | 9.8 | 51 | 704 | |
| 235/55R18 | SL | BSW | 100V | 6.5-(7.5)-8.5 | 11.1 | 28.1 | 9.6 | 51 | 738 | |
| 235/60R18 | XL | BSW | 107V | 6.5-(7.0)-8.5 | 11.2 | 29.1 | 9.4 | 50 | 714 | |
| P235/65R18 | SL | BSW | 104H | 6.5-(7.0)-8.5 | 11.3 | 30.0 | 9.4 | 51 | 692 | |
| 245/60R18 | SL | BSW | 105H | (7.0)-8.5 | 11.3 | 29.6 | 9.8 | 51 | 703 | |
| 255/55R18 | XL | BSW | 109V | 7.0-(8.0)-9.0 | 11.3 | 29.0 | 10.4 | 50 | 716 | |
| P255/65R18 | SL | BSW | 109H | 7.0-(7.5)-9.0 | 11.3 | 31.1 | 10.2 | 51 | 669 | |
| 265/60R18 | SL | BSW | 110V | 7.5-(8.0)-9.5 | 11.3 | 30.5 | 10.7 | 51 | 681 | |
| 235/60R19 | SL | BSW | 99H | 6.5-(7.5)-8.5 | 11.1 | 28.3 | 9.6 | 51 | 734 | |
| 235/55R19 | XL | BSW | 105V | 6.5-(7.5)-8.5 | 11.1 | 29.2 | 9.6 | 50 | 712 | |
| P245/65R19 | SL | BSW | 103H | 7.0-(7.5)-8.5 | 11.2 | 29.6 | 10.0 | 51 | 701 | |
| 255/50R19 | XL | BSW | 107V | 7.0-(8.0)-9.0 | 11.3 | 29.1 | 10.4 | 50 | 714 | |
| P255/60R19 | SL | BSW | 108H | 7.0-(7.5)-9.0 | 11.3 | 31.1 | 10.2 | 51 | 669 | |
| 265/50R19 | XL | BSW | 110H | 7.5-(8.5)-9.5 | 11.3 | 29.5 | 10.9 | 50 | 704 | |
| 275/55R19 | SL | BSW | 111V | 7.5-(8.5)-9.5 | 11.3 | 30.9 | 11.2 | 51 | 672 | |
| P235/65R20 | SL | BSW | 102H | 6.5-(7.5)-8.5 | 11.1 | 30.2 | 9.6 | 51 | 689 | |
| P245/50R20 | SL | BSW | 102V | 7.0-(7.5)-8.5 | 11.2 | 29.7 | 10.0 | 51 | 700 | |
| 265/50R20 | SL | BSW | 107V | 7.5-(8.5)-9.5 | 11.3 | 30.5 | 10.9 | 51 | 682 | |

1 Performance claim based upon commissioned third-party test results. Snow braking results based on test of Toyo Celsius CUV 255/55R18 tires from 30 to 0 mph. Ice braking results based on test of Toyo Celsius 215/60R16 tires from 15 to 0 mph. Individual results may vary. For a copy of the test report, write to Toyo Tire U.S.A. Corp., P.O. Box 6052, Cypress, CA 90630.

Speed rated "S"= 112mph, "T"= 118mph, "H"= 130mph. "BSW"= Black Sidewall. Bold designates measuring rim width. For the latest tire information, please visit toyotires.com.



Mountain Snowflake qualified for severe snow conditions. *See your dealer or toyotires.com for details.

