

**TOYO TIRES®**



**LIGHT TRUCK/SUV/CUV**

DURABILITY IN THE SHAPE OF A TIRE



WE ARE MADE TO CARVE OUR OWN PATH.



Whether you're driving down the street or taking it off-road, Toyo Tires gives your light truck or SUV the power to plow through mud, rock, snow, and any terrain that comes your way. Designed for durability and long tread life, our tires are the surefire way to improve performance, from the ground up.

From the aggressive off-road capabilities of the legendary Open Country M/T and the all-new Open Country R/T to the stylish Proxes ST II, Toyo Tires has an option to take your light truck, SUV, or crossover to the next level.

Don't take our word for it. Get proof. Our Toyo Tires No Regrets® Trial Offer\* means you can personally put our tires to the test. So what are you waiting for?

[TOYO TIRES. DRIVEN TO PERFORM.](#)

\*See next page for details.

# COMMITMENT

THERE ARE NO GUARANTEES IN LIFE.

But this is as close as it gets.

Choose your Toyo light truck tires. Try them for up to 500-miles or 45-days, whichever comes first\*. If you're not completely satisfied with the performance of your tires, just return them to the dealer where you bought them. Your dealer will replace the tires or refund the purchase price, including charges for mounting and balancing — it's your choice.

It's that simple.

And you commit to nothing unless you love it.



**OPEN COUNTRY M/T<sup>®</sup>**  
OFF-ROAD MAXIMUM TRACTION TIRE



**OPEN COUNTRY<sup>®</sup> R/T**  
ON-/OFF-ROAD RUGGED TERRAIN TIRE



**OPEN COUNTRY<sup>®</sup> A/T II**  
ON-/OFF-ROAD ALL-TERRAIN TIRE



**OPEN COUNTRY<sup>®</sup> H/T**  
HIGHWAY ALL-SEASON TIRE



**PROXES<sup>®</sup> ST II<sup>™</sup>**  
STREET/SPORT TRUCK ALL-SEASON TIRE



**PROXES<sup>®</sup> S/T**  
STREET/SPORT TRUCK ALL-SEASON TIRE



**VERSADO<sup>®</sup> CUV**  
CUV/SUV TOURING ALL-SEASON TIRE



**M-55<sup>™</sup>**  
ON-/OFF-ROAD COMMERCIAL  
TRACTION TIRE

\*Excludes Open Country M/T and M-55.  
See your dealer or [ToyoTires.com/NoRegrets](http://ToyoTires.com/NoRegrets) for details.

# OPEN COUNTRY M/T<sup>®</sup>

OFF-ROAD MAXIMUM TRACTION TIRE

Designed for enthusiasts who require extra ground clearance, load-carrying capacity, and off-road capability with great on-road performance. This maximum traction tire is known for its long wear, low noise, and aggressive tread pattern.

- Born from off-road racing.
- Competition-proven at Lucas Oil Off Road Racing Series and SCORE International<sup>®</sup> Off-Road Racing.
- Superior uniformity and balance.



Professional driver. Closed course.



[toyotires.com](http://toyotires.com)



## OPEN COUNTRY® R/T

ON-/OFF-ROAD RUGGED TERRAIN TIRE

Off-road performance meets on-road comfort with the all-new Open Country R/T. Built rugged for any terrain, this tire offers excellent off-road traction, durable construction, and aggressive styling. Its ability to tackle dirt, sand, and rocks is inspired by the legendary Open Country M/T, while its quieter ride is a nod to our best-selling Open Country A/T II.

These tires are 100% American-made at the state-of-the-art Toyo Tires factory in Georgia.

- 45,000-mile treadwear warranty.\*
- Excellent off-road traction, durable construction, and aggressive styling.
- Optimized tread design for a quieter ride.
- Dual sidewall design offers two distinct looks for customizing.



\*See your dealer or [toyotires.com](http://toyotires.com) for details.

[toyotires.com](http://toyotires.com)

# OPEN COUNTRY® A/T II

ON-/OFF-ROAD ALL-TERRAIN TIRE

Pavement is optional with these versatile all-terrain tires. Over 40% more tread life than the leading competitors,<sup>^</sup> a blatantly aggressive tread design, and a quiet ride.

- 65,000-mile treadwear warranty on P-Metric and Metric sizes.\*
- 50,000-mile treadwear warranty on LT sizes and flotation sizes.\*
- UTQG 600 A A and 600 A B
- Available in Xtreme sizes, which feature a deeper tread depth, and a more aggressive tread and shoulder design.

# OPEN COUNTRY® H/T

HIGHWAY ALL-SEASON TIRE

Optimal comfort. Quiet performance. Sure handling. This all-season highway tire is designed for light trucks, SUVs, and CUVs.

- 60,000-mile treadwear warranty on P-Metric and Metric sizes.\*
- UTQG 600 A A, 640 A A, and 640 A B
- Available in Tuff Duty sizes, which feature extra-strong three-belt construction, deeper tread depths, and less tread void. Ideal for towing trailers and hauling heavy loads.



\*See your dealer or [toyotires.com](http://toyotires.com) for details.

<sup>^</sup>Mileage projection based upon commissioned third-party test results. Test conducted on LT265/70R17 tires. Individual results may vary. For a copy of the test report, write to Toyo Tire U.S.A Corp., P.O. Box 6052, Cypress, CA 90630.



Built for pickups hauling heavy loads or towing trailers. Available in select sizes.



[toyotires.com](http://toyotires.com)



Professional driver. Closed course.

## PROXES® ST II™

STREET/SPORT TRUCK ALL-SEASON TIRE

Developed for sport trucks, SUVs, and CUVs, the stylish design and advanced tread elements of this premium tire deliver the perfect balance of style and performance. The Proxes ST II provides superb handling, confident all-season performance, consistent wear, and a smooth, quiet ride.

- A stylish tread design.
- Wide grooves for better wet braking and water evacuation.
- Solid center block for excellent dry braking.
- UTQG 420 A A<sup>^</sup>

## PROXES® S/T

STREET/SPORT TRUCK ALL-SEASON TIRE

This low-profile, high-performance tire offers great value in a wide range of weather and road conditions. The Proxes S/T gives sport trucks, SUVs, and CUVs stability and all-season handling plus high performance, long tread life, and a smooth ride.

- Double “v-shaped” tread grooves evacuate water for good all-season performance.
- UTQG 420 A A



\*See your dealer or [toyotires.com](http://toyotires.com) for details.

<sup>^</sup>Tire size 275/45R19 has a UTQG 280 A A.

[toyotires.com](http://toyotires.com)



# VERSADO® CUV

CUV/SUV TOURING ALL-SEASON TIRE

Designed for a smooth, quiet, luxurious ride, this tire provides the enhanced handling and stability required for crossover vehicles. This stylish tire is also more fuel-efficient thanks to a low rolling-resistance tread compound.

- 50,000-mile treadwear warranty.\*
- Luxurious and stylish asymmetric, non-directional tread design.
- Silent Wall™ technology reduces pipe resonance, resulting in a quieter ride.
- UTQG 440 A B and 440 A A

# M-55™

ON-/OFF-ROAD COMMERCIAL TRACTION TIRE

It might be the hardest-working member of your crew. This all-position traction tire was built for excellent mileage and versatility. It delivers through the snowiest, muddiest, and roughest terrain.

- Aggressive lug-and-block tread design provides solid handling and traction.
- Pinned to accept studs to aid in snow traction.





# OPEN COUNTRY M/T®

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL			
31X10.50R15LT C	1090	BSW	7.0-(8.5)-9.0	19.1	31.1	10.7	2270	-	50	667	
33X10.50R15LT C	114P	BSW	7.0-(8.5)-9.0	19.1	32.8	10.9	2600	-	50	632	
33X12.50R15LT C	108P	BSW	8.0-(10.0)-11.0	21.0	33.0	12.8	2205	-	35	628	
33X13.50R15LT C	1090	BSW	8.5-(11.0)	21.0	33.1	13.9	2270	-	35	628	
35X13.50R15LT C	1140	BSW	8.5-(11.0)	21.0	34.8	14.4	2600	-	35	596	
37X14.50R15LT C	1200	BSW	10.0-(12.0)	21.0	36.7	15.6	3080	-	35	566	
LT295/65R16 E	120/116P	BSW	6.0-(6.5)-7.5	18.4	32.0	9.4	3042	2778	80	648	
LT245/75R16 E	120/116P	BSW	6.5-(7.0)-8.0	18.4	30.7	9.9	3042	2778	80	674	
LT255/85R16 E (33X10.00R16) E	123/120P	BSW	6.5-(7.0)-8.0	18.9	33.5	10.2	3415	3085	80	619	
LT265/75R16 E	123P	BSW	7.0-(7.5)-8.0	18.9	31.8	10.8	3415	-	80	651	
LT285/75R16 E (33X11.50R16) E	126P	BSW	7.5-(8.0)-9.0	19.1	33.0	11.6	3740	-	80	628	
LT305/70R16 E (33X12.00R16) E	124P	BSW	8.0-(9.0)-9.5	20.0	33.0	12.2	3525	-	65	628	
LT315/75R16 E (33X12.50R16) E	1270	BSW	8.0-(8.5)-10.0	21.0	34.9	12.9	3860	-	65	595	
LT385/70R16 E (38X14.50R16) D	1380	BSW	10.0-(11.0)-12.0	21.0	37.7	15.6	4190	-	50	550	
LT265/70R17 E	121P	BSW	7.0-(8.0)-8.5	18.9	32.0	10.8	3195	-	80	648	
LT285/70R17 E	121/118P	BSW	7.5-(8.5)-9.0	18.9	33.0	11.5	3195	2910	80	630	
LT285/75R17 E (34X11.50R17) E	121P	BSW	7.5-(8.0)-9.5	19.1	34.1	11.6	3195	-	80	608	
LT295/70R17 E (33X11.50R17) E	128P	BSW	7.5-(8.5)-10.0	19.4	33.5	12.0	3970	-	80	619	
35X12.50R17LT E	1250	BSW	8.5-(10.0)-11.0	21.0	34.8	13.2	3640	-	65	596	
37X13.50R17LT E	1310	BSW	8.5-(11.0)	21.0	37.0	14.6	4300	-	65	560	
40X13.50R17LT C	1210	BSW	8.5-(11.0)	21.0	39.7	14.4	3195	-	35	522	
LT275/65R18 E	123/120P	BSW	7.5-(8.0)-9.0	18.9	32.3	11.0	3415	3085	80	643	
LT275/70R18 E (33X11.00R18) E	125P	BSW	7.0-(8.0)-8.5	19.1	33.6	11.0	3640	-	80	617	
LT285/70R18 E (33X11.50R18) E	127/124Q	BSW	7.5-(8.5)-9.5	18.9	34.1	11.4	3860	3525	80	609	
LT285/75R18 E (35X11.50R18) E	129P	BSW	7.5-(8.0)-9.5	19.1	35.1	11.6	4080	-	80	591	
LT295/70R18 E	129/126P	BSW	7.5-(8.5)-10.0	19.4	34.5	11.8	4080	3750	80	602	
LT315/70R18 E (36X13.00R18) E	127/124Q	BSW	8.0-(9.5)-11.0	20.7	35.7	13.0	3860	3525	65	581	
33X12.50R18LT E	1180	BSW	8.5-(10.0)-11.0	21.0	33.0	12.7	2910	-	65	630	
35X12.50R18LT E	1230	BSW	8.5-(10.0)-11.0	21.0	35.0	13.2	3415	-	65	593	
37X13.50R18LT D	1240	BSW	8.5-(11.0)	21.0	37.0	14.2	3525	-	50	560	
38X13.50R18LT D	1260	BSW	8.5-(11.0)	21.0	37.7	14.3	3750	-	50	550	
38X15.50R18LT D	1280	BSW	11.0-(12.0)-13.0	21.0	37.7	15.9	3970	-	50	550	

Speed rated "P"= 93mph, "Q"= 99mph. "C"= 6-ply rating, "D"= 8-ply rating, "E"= 10-ply rating. "BSW"= Black Sidewall. Bold designates measuring rim width. For the latest tire information, please visit [toyotires.com](http://toyotires.com).

# OPEN COUNTRY M/T®

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL			
LT275/55R20 D	115/112P	BSW	7.5-(8.5)-9.5	19.1	32.1	11.2	2680	2470	65	647	
LT275/65R20 E (34X11.00R20) E	126P	BSW	7.5-(8.0)-9.5	19.1	34.5	11.0	3750	-	80	601	
LT295/55R20 E	123/120P	BSW	8.0-(9.5)-10.0	19.4	33.0	12.2	3415	3085	80	630	
LT295/60R20 E	126/123P	BSW	8.0-(8.5)-10.0	19.4	34.2	11.8	3750	3415	80	608	
LT295/65R20 E	129/126P	BSW	8.0-(8.5)-10.0	19.4	35.4	11.8	4080	3750	80	588	
LT315/60R20 E (35X12.50R20) E	1250	BSW	8.5-(9.5)-11.0	20.7	35.0	12.6	3640	3305	65	593	
33X12.50R20LT E	1140	BSW	8.5-(10.0)-11.0	21.0	33.0	12.6	2600	-	65	630	
35X12.50R20LT E	1210	BSW	8.5-(10.0)-11.0	21.0	35.0	13.0	3195	-	65	592	
37X13.50R20LT E	1270	BSW	8.5-(11.0)	21.0	37.0	14.0	3860	-	65	560	
38X13.50R20LT D	1240	BSW	8.50-(11.0)	21.0	37.0	14.3	3525	-	50	550	
38X15.50R20LT D	1250	BSW	11.0-(12.0)-13.0	21.0	37.7	15.9	3640	-	50	550	
40X15.50R20LT D	1300	BSW	11.0-(12.0)-13.0	21.0	39.7	15.9	4190	-	50	522	
33X12.50R22LT E	1090	BSW	8.5-(10.0)-11.0	18.9	33.0	12.4	2270	-	65	629	
35X12.50R22LT E	1170	BSW	8.5-(10.0)-11.0	21.0	35.0	12.8	2835	-	65	593	
37X13.50R22LT E	1230	BSW	8.5-(11.0)	21.0	37.0	14.0	3420	-	65	560	
40X15.50R22LT D	1270	BSW	11.0-(12.0)-13.0	21.0	39.7	15.9	3860	-	50	522	
37X13.50R24LT E	1200	BSW	8.5-(11.0)	21.0	37.0	13.6	3085	-	65	561	
40X15.50R24LT E	128P	BSW	11.0-(12.0)-14.0	21.0	39.8	15.4	3970	-	65	522	

# OPEN COUNTRY® R/T

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL			
LT285/70R17 E	121/118Q	BSW	7.5-(8.5)-9.0	16.4	33.0	11.5	3195	2910	80	630	
35X12.50R17LT E	1210	BSW	8.5-(10.0)-11.0	18.9	34.8	12.5	3195	-	65	598	
LT285/65R18 E	125/122Q	BSW	8.0-(8.5)-10.0	16.4	32.8	11.5	3640	3305	80	633	
33X12.50R18LT E	1180	BSW	8.5-(10.0)-11.0	18.9	32.8	12.5	2910	-	65	634	
35X12.50R18LT E	1230	BSW	8.5-(10.0)-11.0	18.9	34.8	12.5	3415	-	65	598	
33X12.50R20LT E	1140	BSW	8.5-(10.0)-11.0	18.9	32.8	12.5	2600	-	65	634	
35X12.50R20LT E	1210	BSW	8.5-(10.0)-11.0	18.9	34.8	12.5	3195	-	65	598	
37X12.50R20LT E	1260	BSW	8.5-(10.0)-11.0	18.9	36.8	12.5	3750	-	65	565	

# OPEN COUNTRY® A/T II

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL	MAX PRESSURE (PSI)	
P215/75R15	100S	OWL	5.5-( <b>6.0</b> )-7.0	12.5	27.7	8.5	1742	-	44	751
P225/75R15	102S	OWL	( <b>6.0</b> )-7.5	12.6	28.3	8.8	1874	-	44	734
P235/75R15	108S	OWL	6.0-( <b>6.5</b> )-8.0	12.7	28.9	9.3	2183	-	50	720
LT235/75R15 C	104/101S	OWL	6.0-( <b>6.5</b> )-7.0	15.6	28.9	9.3	1985	1820	50	720
P265/75R15	112S	OWL	7.0-( <b>7.5</b> )-9.0	13.1	30.7	10.5	2469	-	44	677
30X9.50R15LT C	104S	OWL	6.5-( <b>7.0</b> )-8.5	15.6	29.5	9.4	1995	-	50	704
31X10.50R15LT C	109S	OWL	7.0-( <b>8.5</b> )-9.0	16.0	30.5	10.6	2270	-	50	681
P215/70R16	99S	BSW	5.5-( <b>6.5</b> )-7.0	12.5	27.9	8.7	1709	-	44	745
LT215/85R16 E	115/112Q	BSW	5.5-( <b>6.0</b> )-7.0	15.4	30.4	8.5	2680	2470	80	683
P225/70R16	101T	OWL	6.0-( <b>6.5</b> )-7.5	12.6	28.4	9.0	1819	-	44	731
P225/70R16	101T	BSW	6.0-( <b>6.5</b> )-7.5	12.6	28.4	9.0	1819	-	44	731
P225/75R16	104S	BSW	( <b>6.0</b> )-7.5	12.6	29.3	8.8	1984	-	44	709
LT225/75R16 E	115/112Q	BSW	( <b>6.0</b> )-7.0	15.5	29.3	8.8	2680	2470	80	709
P235/70R16	104T	OWL	6.0-( <b>7.0</b> )-8.0	12.7	29.0	9.4	1984	-	44	717
P235/70R16	104T	BSW	6.0-( <b>7.0</b> )-8.0	12.8	29.0	9.4	1984	-	44	717
LT235/85R16 E	120/116R	BSW	6.0-( <b>6.5</b> )-7.5	15.6	31.7	9.3	3042	2778	80	655
P245/70R16	106S	OWL	6.5-( <b>7.0</b> )-8.0	12.9	29.5	9.8	2094	-	44	704
P245/70R16	106S	BSW	6.5-( <b>7.0</b> )-8.0	12.9	29.5	9.8	2094	-	44	704
P245/75R16	109S	OWL	6.5-( <b>7.0</b> )-8.0	12.9	30.5	9.8	2271	-	44	682
P245/75R16	109S	BSW	6.5-( <b>7.0</b> )-8.0	12.9	30.5	9.8	2271	-	44	682
LT245/75R16 C	108/104S	OWL	6.5-( <b>7.0</b> )-8.0	15.7	30.5	9.8	2205	2006	50	682
LT245/75R16 C	108/104S	BSW	6.5-( <b>7.0</b> )-8.0	15.7	30.5	9.8	2205	2006	50	682
LT245/75R16 E	120/116S	OWL	6.5-( <b>7.0</b> )-8.0	15.7	30.5	9.8	3042	2778	80	682
LT245/75R16 E	120/116S	BSW	6.5-( <b>7.0</b> )-8.0	15.7	30.5	9.8	3042	2778	80	682
255/65R16	109H	BSW	7.0-( <b>7.5</b> )-9.0	12.7	29.1	10.2	2271	-	51	715
P255/70R16	109S	OWL	6.5-( <b>7.5</b> )-8.5	13.0	30.1	10.2	2271	-	44	691
P255/70R16	109S	BSW	6.5-( <b>7.5</b> )-8.5	13.0	30.1	10.2	2271	-	44	691
P265/70R16	111T	OWL	7.0-( <b>8.0</b> )-9.0	13.1	30.6	10.7	2403	-	44	678
P265/70R16	111T	BSW	7.0-( <b>8.0</b> )-9.0	13.1	30.6	10.8	2403	-	44	679
P265/75R16	114T	OWL	7.0-( <b>7.5</b> )-9.0	13.1	31.7	10.5	2601	-	44	656
P265/75R16	114T	BSW	7.0-( <b>7.5</b> )-9.0	13.1	31.7	10.5	2601	-	44	656
LT265/75R16 C	112/109T	OWL	7.0-( <b>7.5</b> )-8.0	16.0	31.7	10.5	2470	2270	50	656
LT265/75R16 C	112/109T	BSW	7.0-( <b>7.5</b> )-8.0	16.0	31.7	10.5	2470	2270	50	656
LT265/75R16 E	123/120R	OWL	7.0-( <b>7.5</b> )-8.0	16.0	31.7	10.5	3415	3085	80	656
LT265/75R16 E	123/120R	BSW	7.0-( <b>7.5</b> )-8.0	16.0	31.7	10.5	3415	3085	80	656
LT285/75R16 E	126/123R	OWL	7.5-( <b>8.0</b> )-9.0	16.5	32.8	11.3	3750	3415	80	633
LT285/75R16 E	126/123R	BSW	7.5-( <b>8.0</b> )-9.0	16.5	32.8	11.3	3750	3415	80	633
LT295/75R16 E*	128R	BSW	7.5-( <b>8.0</b> )-9.5	17.1	33.4	11.6	3970	-	80	622
LT305/70R16 E*	124/121R	BSW	8.0-( <b>9.0</b> )-9.5	17.3	32.8	12.2	3525	3195	65	633
LT315/75R16 E*	127/124R	BSW	8.0-( <b>8.5</b> )-11.0	17.4	34.6	12.3	3860	3525	65	601
P235/65R17	103H	BSW	6.5-( <b>7.0</b> )-8.5	12.5	29.1	9.4	1929	-	51	715
P235/75R17	108S	BSW	6.0-( <b>6.5</b> )-8.0	12.7	30.9	9.3	2205	-	44	673
LT235/80R17 E	120/117R	BSW	6.0-( <b>6.5</b> )-7.5	15.6	31.8	9.3	3085	2835	80	653
P245/65R17	105T	OWL	( <b>7.0</b> )-8.5	12.6	29.5	9.8	2039	-	44	704

# OPEN COUNTRY® A/T II

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL			
P245/65R17	105T	BSW	( <b>7.0</b> )-8.5	12.6	29.4	9.8	2039	-	44	705	
P245/70R17	108S	BSW	6.5-( <b>7.0</b> )-8.0	12.9	30.6	9.8	2205	-	44	680	
LT245/70R17 E	119/116R	BSW	6.5-( <b>7.0</b> )-8.0	15.7	30.6	9.8	3000	2755	80	680	
LT245/75R17 E	121/118S	BSW	6.5-( <b>7.0</b> )-7.5	15.7	31.5	9.8	3195	2910	80	660	
P255/70R17	110S	BSW	6.5-( <b>7.5</b> )-8.5	13.0	31.1	10.2	2337	-	44	668	
P265/65R17	110T	BSW	7.5-( <b>8.0</b> )-9.5	12.9	30.5	10.8	2337	-	44	681	
P265/70R17	113S	OWL	7.0-( <b>8.0</b> )-9.0	13.1	31.5	10.7	2535	-	44	659	
P265/70R17	113S	BSW	7.0-( <b>8.0</b> )-9.0	13.1	31.5	10.7	2535	-	44	659	
LT265/70R17 E	121/118S	OWL	7.0-( <b>8.0</b> )-8.5	16.0	31.7	10.7	3195	2910	80	656	
LT265/70R17 E	121/118S	BSW	7.0-( <b>8.0</b> )-8.5	16.0	31.7	10.7	3195	2910	80	656	
P285/70R17	117T	BSW	7.5-( <b>8.5</b> )-9.5	13.4	32.8	11.5	2833	-	44	634	
LT285/70R17 E	121/118S	OWL	7.5-( <b>8.5</b> )-9.0	16.3	32.8	11.5	3195	2910	80	634	
LT285/70R17 E	121/118S	BSW	7.5-( <b>8.5</b> )-9.0	16.3	32.8	11.5	3195	2910	80	634	
LT285/70R17 E*	121/118S	BSW	7.5-( <b>8.0</b> )-9.5	17.0	33.9	11.3	3195	2910	80	614	
35X12.50R17LT E*	121R	BSW	8.5-( <b>10.0</b> )-11.0	17.4	34.5	12.5	3195	-	65	602	
255/55R18	109H	BSW	7.0-( <b>8.0</b> )-9.0	12.7	29.0	10.4	2271	-	50	716	
P255/70R18	112T	BSW	6.5-( <b>7.5</b> )-8.5	13.0	32.1	10.2	2469	-	44	647	
P265/60R18	109T	BSW	7.5-( <b>8.0</b> )-9.5	12.9	30.5	10.7	2271	-	44	681	
P265/65R18	112S	BSW	7.5-( <b>8.0</b> )-9.5	12.9	31.5	10.7	2469	-	44	659	
P265/70R18	114S	BSW	7.0-( <b>8.0</b> )-9.0	13.1	32.6	10.7	2601	-	44	636	
P275/65R18	114T	BSW	7.5-( <b>8.0</b> )-9.5	13.0	32.1	11.0	2601	-	44	647	
LT275/65R18 C	113/110T	OWL	7.5-( <b>8.0</b> )-9.0	16.0	32.1	11.0	2535	2335	50	647	
LT275/65R18 C	113/110T	BSW	7.5-( <b>8.0</b> )-9.0	16.0	32.1	11.0	2535	2335	50	647	
LT275/65R18 E	123/120S	OWL	7.5-( <b>8.0</b> )-9.0	16.0	32.1	11.0	3415	3085	80	647	
LT275/65R18 E	123/120S	BSW	7.5-( <b>8.0</b> )-9.0	16.0	32.1	11.0	3415	3085	80	647	
LT275/70R18 E	125/122S	OWL	7.0-( <b>8.0</b> )-8.5	16.1	33.2	11.0	3640	3305	80	626	
LT275/70R18 E	125/122S	BSW	7.0-( <b>8.0</b> )-8.5	16.1	33.2	11.0	3640	3305	80	626	
285/60R18	120S	BSW	8.0-( <b>8.5</b> )-10.0	13.6	31.5	11.5	3086	-	50	660	
LT285/60R18 E*	125/122S	BSW	8.0-( <b>8.5</b> )-10.0	16.9	32.6	11.5	3640	3305	80	638	
LT285/75R18 E*	129/126S	BSW	7.5-( <b>8.0</b> )-9.5	17.0	34.8	11.3	4080	3750	80	596	
LT295/70R18 E*	129/126S	BSW	7.5-( <b>8.5</b> )-10.0	16.3	34.3	11.8	4080	3750	80	606	
LT325/60R18 E*	124/121S	BSW	9.0-( <b>9.5</b> )-12.0	16.8	33.3	13.0	3525	3195	65	623	
35X12.50R18LT E*	123R	BSW	8.5-( <b>10.0</b> )-11.0	17.0	34.5	12.5	3415	-	65	602	
P275/55R20	111S	BSW	7.5-( <b>8.5</b> )-9.5	13.0	31.9	11.2	2403	-	44	652	
P225/60R20	114T	BSW	7.5-( <b>8.0</b> )-9.5	13.0	33.0	10.9	2601	-	44	630	
LT275/65R20 E	126/123S	BSW	7.5-( <b>8.0</b> )-9.5	16.0	34.1	11.0	3750	3415	80	609	
LT285/55R20 E*	122/119S	BSW	8.0-( <b>9.0</b> )-10.0	16.0	32.4	11.7	3305	3000	80	642	
LT295/60R20 E*	123/120S	BSW	8.0-( <b>9.5</b> )-10.0	16.3	32.8	12.2	3415	3085	80	634	
LT295/60R20 E*	126/123S	BSW	8.0-( <b>8.5</b> )-10.0	16.4	33.9	11.8	3750	3415	80	612	
LT295/65R20 E*	129/126S	BSW	8.0-( <b>8.5</b> )-10.0	17.0	35.1	11.8	4080	3750	80	592	
305/50R20	120S	BSW	8.5-( <b>9.5</b> )-11.0	13.9	32.0	12.4	3086	-	50	648	
LT305/55R20 E*	121/118S	BSW	8.5-( <b>9.5</b> )-11.0	16.3	33.2	12.4	3195	2910	65	625	
35X12.50R20LT E*	121R	BSW	8.5-( <b>10.0</b> )-11.0	16.8	34.5	12.5	3195	-	65	602	
LT325/50R22 E*	122R	BSW	9.0-( <b>10.0</b> )-12.0	17.0	34.8	13.2	3305	-	65	596	

Speed rated "Q" = 99mph, "R" = 106mph, "S" = 112mph, "T" = 118mph, "H" = 130mph.  
 "\*\*\*\*" = Xtreme. "C" = 6-ply rating, "E" = 10-ply rating. "BSW" = Black Sidewall,  
 "OWL" = Outline White Lettering. Bold designates measuring rim width.  
 For the latest tire information, please visit toyotires.com.

# OPEN COUNTRY® H/T

## SPECIFICATIONS

# OPEN COUNTRY® H/T

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS		MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL		
P225/70R15	100T	OWL	<b>6.0</b> -( <b>6.5</b> )-7.5	12.6	27.4	8.9	1753	-	35	757
P225/75R15	102S	OWL	<b>(6.0)</b> -7.5	12.6	28.3	8.9	1874	-	35	733
P235/70R15	102S	OWL	<b>6.0</b> -( <b>7.0</b> )-8.0	12.7	28.0	9.4	1896	-	35	743
P235/75R15	105S	OWL	<b>6.0</b> -( <b>6.5</b> )-8.0	12.7	28.9	9.3	2028	-	35	719
LT235/75R15 C	104/101S	OWL	<b>6.0</b> -( <b>6.5</b> )-7.0	14.0	28.8	9.5	1985	1820	50	722
P245/70R15	110S	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	29.6	10.4	2337	-	35	702
31X10.50R15LT C	109S	OWL	<b>7.0</b> -( <b>8.5</b> )-9.0	15.6	30.3	10.9	2270	-	50	685
215/65R16	98H	BSW	<b>6.0</b> -( <b>6.5</b> )-7.5	12.2	27.0	8.8	1653	-	44	770
P215/70R16	99H	BSW	<b>5.5</b> -( <b>6.5</b> )-7.0	12.5	27.9	8.7	1709	-	35	744
LT215/85R16 E	115/112S	BSW	<b>5.5</b> -( <b>6.0</b> )-7.0	15.0	30.4	8.9	2680	2470	80	683
P225/70R16	101T	OWL	<b>6.0</b> -( <b>6.5</b> )-7.5	12.6	28.4	9.0	1819	-	35	731
P225/75R16	104S	OWL	<b>(6.0)</b> -7.5	12.6	29.3	8.9	1984	-	35	708
LT225/75R16 E	115/112S	BSW	<b>(6.0)</b> -7.0	13.9	29.3	9.1	2680	2470	80	710
235/60R16	100H	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	27.1	9.4	1764	-	44	767
P235/65R16	101S	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	28.0	9.6	1819	-	35	741
P235/70R16	104T	OWL	<b>6.0</b> -( <b>7.0</b> )-8.0	12.7	28.9	9.3	1984	-	35	718
P235/75R16	106S	OWL	<b>6.0</b> -( <b>6.5</b> )-8.0	12.9	29.8	9.4	2094	-	35	697
LT235/85R16 E	120/116S	OWL	<b>6.0</b> -( <b>6.5</b> )-7.5	15.2	31.8	9.4	3042	2778	80	654
LT235/85R16 E*	120/116Q	BSW	<b>6.0</b> -( <b>6.5</b> )-7.5	15.9	31.6	9.2	3042	2778	80	657
P245/70R16	106S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	12.9	29.4	9.6	2094	-	35	706
P245/75R16	109S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	12.9	30.4	9.8	2271	-	35	683
LT245/75R16 E	120/116S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	15.2	30.4	9.8	3042	2778	80	684
LT245/75R16 E*	120/116R	BSW	<b>6.5</b> -( <b>7.0</b> )-8.0	15.9	30.6	9.9	3042	2778	80	680
255/65R16	109H	BSW	<b>7.0</b> -( <b>7.5</b> )-9.0	12.7	29.1	10.2	2271	-	44	715
P255/70R16	109S	OWL	<b>6.5</b> -( <b>7.5</b> )-8.5	13.0	30.0	10.1	2271	-	35	692
P265/70R16	111S	OWL	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	30.6	10.4	2403	-	35	678
P265/75R16	114T	OWL	<b>7.0</b> -( <b>7.5</b> )-9.0	13.1	31.5	10.4	2601	-	35	659
LT265/75R16 C	112/109S	OWL	<b>7.0</b> -( <b>7.5</b> )-8.0	15.6	31.6	10.8	2470	2270	50	658
LT265/75R16 D	119/116S	OWL	<b>7.0</b> -( <b>7.5</b> )-8.0	15.6	31.6	10.8	3000	2755	65	658
LT265/75R16 E	123/120S	OWL	<b>7.0</b> -( <b>7.5</b> )-8.0	15.6	31.6	10.8	3415	3085	80	658
LT265/75R16 E*	123/120Q	BSW	<b>7.0</b> -( <b>7.5</b> )-8.0	16.3	31.6	10.6	3415	3085	80	658
P275/70R16	114H	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	13.2	31.1	10.8	2601	-	35	667
LT285/75R16 E	126/123S	OWL	<b>7.5</b> -( <b>8.0</b> )-9.0	16.5	32.8	11.4	3750	3415	80	633
LT285/75R16 E*	126/123Q	BSW	<b>7.5</b> -( <b>8.0</b> )-9.0	17.1	32.8	11.3	3750	3415	80	632
225/65R17	102H	BSW	<b>6.0</b> -( <b>6.5</b> )-8.0	12.3	28.5	8.9	1874	-	44	729
LT225/75R17 E*	116/113Q	BSW	<b>(6.0)</b> -7.5	14.5	30.3	8.7	2755	2535	80	685
P235/60R17	100S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.5	11.3	28.2	9.4	1764	-	35	737
P235/60R17	100S	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	28.2	9.4	1764	-	35	737
235/65R17	104H	OWL	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	29.0	9.4	1984	-	44	716
235/65R17	104H	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	29.1	9.4	1984	-	44	713
P235/70R17	108S	OWL	<b>6.0</b> -( <b>7.0</b> )-8.0	12.7	29.9	9.4	2205	-	41	695
P235/70R17	108S	BSW	<b>6.0</b> -( <b>7.0</b> )-8.0	12.7	29.9	9.4	2205	-	41	695
P235/75R17	108S	OWL	<b>6.0</b> -( <b>6.5</b> )-8.0	12.9	30.9	9.5	2205	-	35	673
LT235/80R17 E	120/117S	BSW	<b>6.0</b> -( <b>6.5</b> )-7.5	15.2	31.7	9.2	3085	2835	80	655
LT235/80R17 E*	120/117R	BSW	<b>6.0</b> -( <b>6.5</b> )-7.5	15.9	31.8	9.2	3085	2835	80	653
P245/65R17	105H	OWL	<b>(7.0)</b> -8.5	12.6	29.5	9.7	2039	-	35	704

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS		MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL		
P245/65R17	105H	BSW	<b>(7.0)</b> -8.5	12.6	29.5	9.7	2039	-	35	704
P245/70R17	108S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	12.9	30.6	9.8	2205	-	35	680
P245/70R17	108S	BSW	<b>6.5</b> -( <b>7.0</b> )-8.0	12.9	30.4	9.8	2205	-	35	683
LT245/70R17 E	119/116S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	15.4	30.5	9.8	3000	2755	80	681
LT245/70R17 E	119/116S	BSW	<b>6.5</b> -( <b>7.0</b> )-8.0	15.4	30.6	9.9	3000	2755	80	678
P245/75R17	110S	OWL	<b>6.5</b> -( <b>7.0</b> )-8.0	12.9	31.5	9.8	2337	-	35	660
LT245/75R17 E	121/118S	OWL	<b>6.5</b> -( <b>7.0</b> )-7.5	15.2	31.5	9.9	3195	2910	80	660
LT245/75R17 E	121/118S	BSW	<b>6.5</b> -( <b>7.0</b> )-7.5	15.2	31.5	9.8	3195	2910	80	660
LT245/75R17 E*	121/118S	BSW	<b>6.5</b> -( <b>7.0</b> )-7.5	15.9	31.5	9.8	3195	2910	80	660
255/60R17	106H	BSW	<b>7.0</b> -( <b>7.5</b> )-9.0	12.9	29.1	10.3	2094	-	44	715
P255/65R17	108S	OWL	<b>7.0</b> -( <b>7.5</b> )-9.0	12.7	30.1	10.3	2205	-	35	691
P255/65R17	108S	BSW	<b>7.0</b> -( <b>7.5</b> )-9.0	12.7	30.1	10.4	2205	-	35	691
P255/70R17	110S	OWL	<b>6.5</b> -( <b>7.5</b> )-8.5	13.0	31.1	10.3	2337	-	35	668
P255/70R17	110S	BSW	<b>6.5</b> -( <b>7.5</b> )-8.5	13.0	31.1	10.3	2337	-	35	668
P265/65R17	110S	OWL	<b>7.5</b> -( <b>8.0</b> )-9.5	12.9	30.5	10.6	2337	-	35	682
P265/65R17	110S	BSW	<b>7.5</b> -( <b>8.0</b> )-9.5	12.9	30.6	10.8	2337	-	35	680
P265/70R17	113T	OWL	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	31.5	10.7	2535	-	35	659
P265/70R17	113T	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	31.5	10.8	2535	-	35	660
LT265/70R17 E	121/118S	OWL	<b>7.0</b> -( <b>8.0</b> )-8.5	15.6	31.6	10.7	3195	2910	80	658
LT265/70R17 E	121/118S	BSW	<b>7.0</b> -( <b>8.0</b> )-8.5	15.6	31.6	10.7	3195	2910	80	658
LT265/70R17 E*	121/118R	BSW	<b>7.0</b> -( <b>8.0</b> )-8.5	16.3	31.5	10.8	3195	2910	80	660
P285/70R17	117T	BSW	<b>7.5</b> -( <b>8.5</b> )-9.5	13.4	32.7	11.4	2833	-	35	636
LT285/70R17 E	121/118S	OWL	<b>7.5</b> -( <b>8.5</b> )-9.0	16.5	32.7	11.7	3195	2910	80	636
235/65R18	100V	BSW	<b>6.5</b> -( <b>7.5</b> )-8.5	10.1	28.2	9.6	1764	-	44	738
235/60R18	107V	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	10.7	29.1	9.4	2150	-	50	714
P235/65R18	104T	BSW	<b>6.5</b> -( <b>7.0</b> )-8.5	12.5	30.2	9.6	1984	-	35	689
P245/60R18	104H	BSW	<b>(7.0)</b> -8.5	12.6	29.6	9.6	1984	-	35	701
255/65R18	109V	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	12.2	29.1	10.4	2271	-	50	715
255/60R18	112H	BSW	<b>7.0</b> -( <b>7.5</b> )-9.0	12.7	30.0	10.1	2469	-	50	692
P255/65R18	109S	BSW	<b>7.0</b> -( <b>7.5</b> )-9.0	11.6	31.1	10.2	2271	-	44	669
255/70R18	113S	BSW	<b>6.5</b> -( <b>7.5</b> )-8.5	11.8	32.2	10.4	2535	-	44	646
P265/60R18	109T	OWL	<b>7.0</b> -( <b>8.0</b> )-9.5	12.9	30.5	10.6	2271	-	35	682
P265/60R18	109T	BSW	<b>7.5</b> -( <b>8.0</b> )-9.5	12.9	30.5	10.8	2271	-	35	681
P265/65R18	112S	BSW	<b>7.5</b> -( <b>8.0</b> )-9.5	12.9	31.5	10.7	2469	-	35	660
P265/70R18	114S	OWL	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	32.6	10.8	2601	-	35	636
P265/70R18	114S	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	13.1	32.6	10.8	2601	-	35	636
LT265/70R18 E*	124/121R	BSW	<b>7.0</b> -( <b>8.0</b> )-9.0	16.3	32.6	10.7	3525	3195	80	636
P275/60R18	111H	BSW	<b>7.5</b> -( <b>8.0</b> )-9.5	13.0	30.8	10.9	2403	-	35	675
P275/65R18	114T	OWL	<b>7.5</b> -( <b>8.0</b> )-9.5	13.0	32.2	11.0	2601	-	35	646
P275/65R18	114T	BSW	<b>7.5</b> -( <b>8.0</b> )-9.5	13.0	32.2	11.0	2601	-	35	646
LT275/65R18 E	123S	OWL	<b>7.5</b> -( <b>8.0</b> )-9.0	15.6	32.0	10.9	3415	-	80	650
LT275/65R18 E	123S	BSW	<b>7.5</b> -( <b>8.0</b> )-9.0	15.6	32.0	10.9	3415	-	80	650
LT275/65R18 E*	123/120S	BSW	<b>7.5</b> -( <b>8.0</b> )-9.0	16.3	32.1	11.0	3415	3085	80	647
LT275/70R18 E	125S	OWL	<b>7.0</b> -( <b>8.0</b> )-8.5	15.6	33.1	11.0	3640	-	80	628
LT275/70R18 E	125S	BSW	<b>7.0</b> -( <b>8.0</b> )-8.5	15.6	33.1	11.2	3640	-	80	628
LT275/70R18 E*	125/122S	BSW	<b>7.0</b> -( <b>8.0</b> )-8.5	16.3	33.2	11.0	3640	3305	80	626

Speed rated "Q"= 99mph, "R"= 106mph, "S"= 112mph, "T"= 118mph, "H"= 130mph, "V"= 149mph, "\*"= Tuff Duty, "C"= 6-ply rating, "D"= 8-ply rating, "E"= 10-ply rating. "BSW"= Black Sidewall, "OWL"= Outline White Lettering. Bold designates measuring rim width. For the latest tire information, please visit [toyotires.com](http://toyotires.com).

# OPEN COUNTRY® H/T

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL	MAX PRESSURE (PSI)	
P245/55R19	103S	BSW	7.0-(7.5)-8.5	12.6	29.7	9.6	1929	-	44	700
255/55R19	111V	BSW	7.0-(8.0)-9.0	12.2	30.0	10.4	2403	-	50	692
255/60R19	109H	BSW	7.0-(7.5)-9.0	12.7	31.1	10.2	2271	-	44	669
P235/55R20	102T	BSW	6.5-(7.5)-8.5	12.5	30.2	9.4	1874	-	44	687
P245/50R20	102V	BSW	7.0-(7.5)-8.5	11.8	29.7	10.0	1874	-	44	700
P255/55R20	107H	BSW	7.0-(8.0)-9.0	12.7	31.0	10.4	2149	-	44	670
265/50R20	111V	BSW	7.5-(8.5)-9.5	10.8	30.4	10.9	2403	-	50	683
275/55R20	117S	DWL	7.5-(8.5)-9.5	13.0	31.9	11.4	2833	-	50	651
P275/60R20	114S	DWL	7.5-(8.0)-9.5	13.0	33.1	10.9	2601	-	35	627
285/45R22	114H	BSW	8.0-(9.5)-10.5	12.2	32.0	11.2	2601	-	50	648

# PROXES® ST II™

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL	MAX PRESSURE (PSI)	
265/70R16	112V	BSW	7.0-(8.0)-9.0	11.2	30.6	10.9	2469	-	51	679
275/60R16	109V	BSW	7.5-(8.0)-9.5	11.2	28.9	10.9	2271	-	51	719
225/55R17	97V	BSW	6.0-(7.0)-8.0	10.6	26.7	9.1	1609	-	51	777
235/65R17	104V	BSW	6.5-(7.0)-8.5	10.7	29.0	9.3	1984	-	51	717
255/60R17	110V	BSW	7.0-(7.5)-9.0	11.0	29.0	10.1	2337	-	50	717
275/55R17	109V	BSW	7.5-(8.5)-9.5	11.2	28.9	10.9	2271	-	51	720
275/60R17	110V	BSW	7.5-(8.0)-9.5	11.2	29.9	10.8	2337	-	51	694
285/60R17	114V	BSW	8.0-(8.5)-10.0	11.3	30.4	11.4	2601	-	51	684
255/45R18	99V	BSW	8.0-(8.5)-9.5	10.3	27.0	9.8	1709	-	51	769
255/50R18	106V	BSW	7.0-(8.0)-9.0	10.8	28.1	10.2	2094	-	50	813
255/55R18	109V	BSW	7.0-(8.0)-9.0	11.0	29.0	10.2	2271	-	50	717
255/60R18	112V	BSW	7.0-(7.5)-9.0	11.0	30.0	9.9	2469	-	50	693
285/60R18	116V	BSW	8.0-(8.5)-10.0	11.3	31.3	11.3	2756	-	51	663
295/45R18	108V	BSW	9.5-(10.0)-11.0	10.8	28.3	11.4	2205	-	51	733
255/50R19	103V	BSW	7.0-(8.0)-9.0	10.8	29.1	10.2	1929	-	51	715
255/55R19	111V	BSW	7.0-(8.0)-9.0	11.0	30.0	10.3	2403	-	50	693
275/45R19	108Y	BSW	8.5-(9.0)-10.5	10.1	28.7	10.7	2205	-	50	724
285/45R19	111V	BSW	9.0-(9.5)-10.5	10.7	29.1	11.2	2403	-	50	714
245/50R20	102V	BSW	7.0-(7.5)-8.5	10.7	29.7	10.0	1874	-	51	698
255/40R20	101V	BSW	8.5-(9.0)-10.0	10.3	28.0	10.0	1819	-	50	741
255/45R20	105V	BSW	8.0-(8.5)-9.5	10.3	29.0	9.9	2039	-	50	716
255/50R20	109V	BSW	7.0-(8.0)-9.0	10.8	30.0	10.2	2271	-	50	692
265/45R20	108V	BSW	8.5-(9.0)-10.0	10.5	29.4	10.2	2205	-	50	707
265/50R20	111V	BSW	7.5-(8.5)-9.5	11.0	30.4	10.8	2403	-	50	683
275/40R20	106W	BSW	9.0-(9.5)-11.0	10.6	28.7	10.7	2094	-	50	725
275/45R20	110V	BSW	8.5-(9.0)-10.5	10.6	29.7	10.6	2337	-	50	700
275/55R20	117V	BSW	7.5-(8.5)-9.5	11.2	31.8	10.9	2833	-	50	653
285/50R20	116V	BSW	8.0-(9.0)-10.0	11.2	31.2	11.4	2756	-	50	665
295/40R20	106V	BSW	10.0-(10.5)-11.5	10.8	29.3	11.7	2094	-	51	710
295/45R20	114V	BSW	9.5-(10.0)-11.0	10.8	30.4	11.6	2601	-	50	683
305/50R20	120V	BSW	8.5-(9.5)-11.0	11.5	32.0	12.1	3086	-	50	649
315/35R20	110W	BSW	10.5-(11.0)-12.5	11.1	28.6	12.2	2337	-	50	726
265/35R22	102W	BSW	9.0-(9.5)-10.5	10.5	29.3	10.5	1874	-	50	709
265/40R22	106V	BSW	9.0-(9.5)-10.5	10.5	30.3	10.5	2094	-	50	686
265/45R22	109V	BSW	8.5-(9.0)-10.0	10.5	31.4	10.3	2271	-	50	661
285/35R22	106W	BSW	9.5-(10.0)-11.0	10.7	29.8	11.2	2094	-	50	698
285/40R22	110V	BSW	9.5-(10.0)-11.0	10.7	31.0	11.1	2337	-	50	669
285/45R22	114V	BSW	9.0-(9.5)-10.5	10.7	32.0	11.1	2601	-	50	648
LT285/50R22 E	121H	BSW	8.0-(9.0)-10.0	13.0	33.1	11.2	3195	-	80	628
305/40R22	114V	BSW	10.0-(11.0)-12.0	11.0	31.6	12.1	2601	-	50	657
305/45R22	118V	BSW	9.5-(10.0)-11.5	11.0	32.8	11.8	2910	-	50	634
305/40R23	115V	BSW	10.0-(11.0)-12.0	11.0	32.5	12.2	2679	-	50	639
285/40R24	112V	BSW	9.5-(10.0)-11.0	10.7	32.9	11.7	2469	-	50	631
295/30R24	105V	BSW	10.0-(10.5)-11.0	10.8	31.0	11.1	2039	-	50	670
305/35R24	112V	BSW	10.0-(11.0)-12.0	11.0	32.4	12.1	2469	-	50	640

Speed rated "Q"= 99mph, "R"= 106mph, "S"= 112mph, "T"= 118mph, "H"= 130mph, "V"= 149mph, "W"= 168mph, "Y"= 186mph. "C"= 6-ply rating, "D"= 8-ply rating, "E"= 10-ply rating. "BSW"= Black Sidewall, "OWL"= Outline White Lettering. Bold designates measuring rim width. For the latest tire information, please visit [toyotires.com](http://toyotires.com).

# PROXES® S/T

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS		MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL		
265/50R20	111V	BSW	7.5-( <b>8.5</b> )-9.5	11.3	30.4	11.0	2403	-	50	683
275/40R20	106W	BSW	9.0-( <b>9.5</b> )-11.0	10.6	28.6	10.8	2094	-	50	727
275/45R20	110V	BSW	8.5-( <b>9.0</b> )-10.5	10.7	29.8	10.6	2337	-	50	698
275/55R20	117V	BSW	7.5-( <b>8.5</b> )-9.5	11.2	31.9	11.0	2833	-	50	652
285/50R20	116V	BSW	8.0-( <b>9.0</b> )-10.0	10.8	31.1	11.6	2756	-	50	669
295/45R20	114V	BSW	9.5-( <b>10.0</b> )-11.0	11.0	30.5	11.7	2601	-	50	683
305/50R20	120V	BSW	8.5-( <b>9.5</b> )-11.0	11.5	32.1	12.4	3086	-	50	651
245/35R22	102W	BSW	9.0-( <b>9.5</b> )-10.5	10.5	29.3	10.4	1874	-	50	708
265/40R22	106V	BSW	9.0-( <b>9.5</b> )-10.5	10.5	30.4	10.7	2094	-	50	684
285/45R22	114V	BSW	9.0-( <b>9.5</b> )-10.5	10.8	32.2	11.2	2601	-	50	645
305/40R22	114V	BSW	10.0-( <b>10.5</b> )-12.0	11.0	31.6	12.3	2601	-	50	657
305/45R22	118V	BSW	9.5-( <b>10.0</b> )-11.5	11.0	32.8	12.0	2910	-	50	636
305/35R24	112V	BSW	10.0-( <b>11.0</b> )-12.0	11.0	32.5	12.1	2469	-	50	640

# M-55™

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS		MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL		
LT215/75R15 C	100/97M	BSW	5.5-( <b>6.0</b> )-7.0	17.0	27.7	8.5	1765	1610	50	738
LT235/75R15 C	104/101M	BSW	6.0-( <b>6.5</b> )-7.0	17.6	28.9	9.3	1985	1820	50	710
LT215/85R16 E	115/112N	BSW	5.5-( <b>6.0</b> )-7.0	16.9	30.7	8.6	2680	2470	80	676
LT225/75R16 E	115/112N	BSW	( <b>6.0</b> )-7.0	16.9	29.4	8.5	2680	2470	80	706
LT235/85R16 E	120/116N	BSW	6.0-( <b>6.5</b> )-7.5	17.5	32.0	9.3	3042	2778	80	649
LT245/75R16 E	120/116N	BSW	6.5-( <b>7.0</b> )-8.0	17.5	30.7	9.8	3042	2778	80	675
LT255/85R16 E	123/120M	BSW	6.5-( <b>7.0</b> )-8.0	18.1	33.3	10.4	3415	3085	80	624
LT265/75R16 E	123/120N	BSW	7.0-( <b>7.5</b> )-8.0	18.2	31.9	10.8	3415	3085	80	651
LT285/75R16 E	126/123M	BSW	7.5-( <b>8.0</b> )-9.0	18.9	33.2	11.3	3740	3415	80	625
LT235/80R17 E	120/117N	BSW	6.0-( <b>6.5</b> )-7.5	17.5	31.9	9.3	3085	2835	80	651
LT245/75R17 E	121/118N	BSW	6.5-( <b>7.0</b> )-7.5	17.5	31.9	9.7	3195	2910	80	651
LT265/70R17 E	121/118N	BSW	7.0-( <b>8.0</b> )-8.5	18.1	31.9	10.6	3195	2910	80	650
LT275/70R18 E	125/122N	BSW	7.0-( <b>8.0</b> )-8.5	18.8	33.6	11.0	3640	3305	80	618

Speed rated "M" = 81mph, "N" = 87mph, "S" = 112mph, "T" = 118mph, "H" = 130mph, "V" = 149mph, "W" = 168mph. "C" = 6-ply rating, "E" = 10-ply rating. "BSW" = Black Sidewall. Bold designates measuring rim width. For the latest tire information, please visit [toyotires.com](http://toyotires.com).

# VERSADO® CUV

## SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS		MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)			
P235/70R16	104T	BSW	6.0-( <b>7.0</b> )-8.0	11.0	28.9	9.4	1984	44	719
P215/65R17	98T	BSW	6.0-( <b>6.5</b> )-7.5	10.3	28.0	8.6	1653	44	742
P225/60R17	98V	BSW	6.0-( <b>6.5</b> )-8.0	10.3	27.7	9.0	1653	51	749
225/60R17	102H	BSW	6.0-( <b>6.5</b> )-8.0	10.5	28.5	8.8	1874	51	729
235/55R17	99H	BSW	6.5-( <b>7.5</b> )-8.5	10.3	27.1	9.6	1709	51	767
235/60R17	102T	BSW	6.5-( <b>7.0</b> )-8.5	10.5	28.1	9.3	1874	44	740
235/65R17	104H	BSW	6.5-( <b>7.0</b> )-8.5	10.6	29.1	9.3	1984	51	715
235/65R17	108V	BSW	6.5-( <b>7.0</b> )-8.5	10.6	29.0	9.4	2205	50	716
245/55R17	102V	BSW	7.0-( <b>7.5</b> )-8.5	10.5	27.6	10.0	1874	51	752
255/60R17	106V	BSW	7.0-( <b>7.5</b> )-9.0	10.7	29.1	10.3	2094	51	715
215/55R18	95T	BSW	6.0-( <b>7.0</b> )-7.5	10.1	27.3	8.8	1521	44	760
225/55R18	98V	BSW	6.0-( <b>7.0</b> )-8.0	10.2	27.8	9.0	1653	51	747
235/50R18	97V	BSW	6.5-( <b>7.5</b> )-8.5	10.3	27.3	9.3	1609	51	760
235/55R18	100V	BSW	6.5-( <b>7.5</b> )-8.5	10.3	28.2	9.4	1764	51	735
235/60R18	107V	BSW	6.5-( <b>7.0</b> )-8.5	10.5	29.1	9.4	2149	50	715
235/65R18	106T	BSW	6.5-( <b>7.0</b> )-8.5	10.6	30.0	9.3	2094	44	692
245/60R18	105H	BSW	( <b>7.0</b> )-8.5	10.6	29.7	9.5	2039	51	700
255/55R18	109V	BSW	7.0-( <b>8.0</b> )-9.0	10.6	28.9	10.2	2271	50	718
P255/65R18	109S	BSW	7.0-( <b>7.5</b> )-9.0	10.8	31.1	10.0	2271	44	669
265/60R18	110V	BSW	7.5-( <b>8.0</b> )-9.5	10.8	30.5	10.6	2337	51	681
P225/55R19	99V	BSW	6.0-( <b>7.0</b> )-8.0	10.2	28.8	9.2	1709	51	722
235/50R19	99H	BSW	6.5-( <b>7.5</b> )-8.5	10.3	28.5	9.4	1709	51	729
235/55R19	105V	BSW	6.5-( <b>7.5</b> )-8.5	10.3	29.2	9.5	2039	50	711
P245/55R19	103T	BSW	7.0-( <b>7.5</b> )-8.5	10.5	29.6	9.7	1929	44	701
255/50R19	107V	BSW	7.0-( <b>8.0</b> )-9.0	10.6	29.1	10.3	2149	50	714
P255/60R19	108H	BSW	7.0-( <b>7.5</b> )-9.0	10.7	31.0	10.2	2205	51	669
265/50R19	110V	BSW	7.5-( <b>8.5</b> )-9.5	10.7	29.4	10.8	2337	50	706
275/55R19	111V	BSW	7.5-( <b>8.5</b> )-9.5	10.8	30.9	11.0	2403	51	673
P235/55R20	102T	BSW	6.5-( <b>7.5</b> )-8.5	10.3	30.2	9.6	1874	44	688
P245/50R20	102V	BSW	7.0-( <b>7.5</b> )-8.5	10.5	29.7	9.8	1874	51	700
P255/50R20	104H	BSW	7.0-( <b>8.0</b> )-9.0	10.6	30.1	10.4	1984	51	691
P255/55R20	107H	BSW	7.0-( <b>8.0</b> )-9.0	10.6	31.0	10.4	2149	51	670
265/50R20	107V	BSW	7.5-( <b>8.5</b> )-9.5	10.7	30.5	10.8	2149	51	681



**WARNING!**

**TIRES MUST NEVER BE OPERATED IN EXCESS OF THEIR RATED SPEED LIMIT.**

Exceeding the tire's speed capability will cause overheating of the tire and sudden failure, possibly leading to loss of vehicle control. Toyo Tires passenger and light truck tires have a maximum speed rating depending on size and type. Consult your tire dealer or contact Toyo Tires at 800.442.8696 if you are not sure about the maximum speed rating of your tires. Toyo Tire U.S.A. Corp. does not endorse the operation of any vehicle in an unsafe or unlawful manner. Tire speed ratings do not imply that a vehicle can be safely driven at the speed for which the tire is rated. Speed ratings are based on laboratory tests, which relate to performance on the road, but are not applicable if tires are underinflated, overloaded, worn out, damaged, or altered.

**EXERCISE DUE CARE WHEN OPERATING VEHICLES WITH MODIFIED SUSPENSIONS AND INCREASED GROUND CLEARANCE!**

The installation of off-road type tires, combined with modified suspensions and increased ground clearance, can significantly alter the handling characteristics of a vehicle, including increased braking distances and changes to vehicle maneuverability and cornering capability. Such modified vehicles will perform differently from stock models. If you make sharp turns or abrupt maneuvers, the vehicle may roll over or go out of control and crash. Always wear seat belts and drive safely, recognizing that reduced speeds and specialized driving techniques may be required. You should read the driving guidelines and instructions in the owner's manuals provided by the manufacturers of both the vehicle and the suspension kit.

**ALWAYS OBEY ALL VEHICLE AND TRAFFIC LAWS!**

You are responsible for the legality and safety of any modifications to your vehicle, and for operating your vehicle in a safe and lawful manner. Consult your vehicle owner's manual, your local laws, and the vehicle suspension kit manufacturer before undertaking modifications to your vehicle suspension.

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials specifications, or availability without notice or obligation.



**TOYO TIRES<sup>®</sup>**

**TOYOTIRES.COM**

TOYO TIRE U.S.A. CORP.  
P.O. BOX 6052  
CYPRESS, CA 90630  
800.442.8696



©2014 Toyo Tire U.S.A. Corp.  
Published July 2014

#0180113